






Flexible Grinding Wheel



RESIBON FLEXIBLE GRINDING WHEELS

Combine the advantages of depressed center grinding wheels and resin fiber discs (sanding discs). Because of their flexibility, they put more grinding surface on the job and will grind faster and last longer. Flexibility also enables a closer fit between the wheel and the job, which results in a smoother finish. There is also less vibration and operator fatigue with a flexible grinding wheel.



For General Steel

METAL 	NAME	SIZE		SPEC					MAX OPERATING SPEED		CARTON Q'ty	Origin	
		mm	inch	Grain	36	46	60	80	120	m/s			rpm(min-1)
Type-27 	MS	50x2x9.53	2x5/64x3/8	#						72	27,500	250	J
		58x3x9.53	2-5/16x1/8x3/8								23,700	250	
	BEST TOUCH 	AC	100x2x16	4x5/64x5/8						72	13,700	200	J/T
			100x3x16	4x1/8x5/8							13,700	200	
			115x3x22.23	4-1/2x1/8x7/8							13,300	160	
			125x3x22.23	5x1/8x7/8							12,200	160	
			180x3x22.23	7x1/8x7/8							8,500	75	
			230x3x22.23	9x1/8x7/8							6,600	75	

MS : Mini Skill  : Always use backup pad


*Origin: J = Japan T = Thailand J/T = Japan & Thailand

For Stainless Steel / INOX

STAINLESS	NAME	SIZE		SPEC					MAX OPERATING SPEED		CARTON Q'ty	Origin	
		mm	inch	Grain	36	46	60	80	120	m/s			rpm(min-1)
 Type-27	GENERAL												
	BEST TOUCH	100x2x16	4x5/64x5/8	WA						72	13,700	200	J/T
		100x3x16	4x1/8x5/8									200	
		115x3x22.23	4-1/2x1/8x7/8		80						13,300	160	
		125x3x22.23	5x1/8x7/8								12,200	160	
		180x3x22.23	7x1/8x7/8								8,500	75	
230x3x22.23		9x1/8x7/8								6,600	75		
SOFT GRINDING / POLISHING													
GA-3	100x3x16	4x1/8x5/8	#						72	13,700	400	J	
HIGH PERFORMANCE													
 Type-27	SRT	100x3x16	4x1/8x5/8	#						72	13,700	200	J
		125x3x22	5x1/8x7/8								11,000	100	
		125X4X22	5x5/32x7/8								11,000	100	
		180X3X22	7x1/8x7/8								7,600	50	
		180X4X22	7x5/32x7/8								7,600	50	

GA-3 : Green Ace Gold SRT : Super Resi Techma

For Stone / Masonry / Glass / Concrete

MASONRY	NAME	SIZE		SPEC					MAX OPERATING SPEED		CARTON Q'ty	Origin	
		mm	inch	Grain	36	46	60	80	120	m/s			rpm(min-1)
 Type-27	GENERAL												
	BEST TOUCH	100x2x16	4x5/64x5/8	GC						72	13,700	200	J/T
		100x3x16	4x1/8x5/8									200	
	CONCRETE												
	BEST TOUCH R-2	125x3x22	5x1/8x7/8	CC16						72	11,000	100	J
		150x3x22	6x1/8x7/8									9,100	
180x3x22.23		7x1/8x7/8							80			8,500	

*Origin: J = Japan T = Thailand J/T = Japan & Thailand